MALTAWARD

RANGE OVERVIEW

GroundTuff® Range

Temporary Ground Protection

Hard-wearing ground protection mats for construction sites, events, car parks and access routes – all year round, from covering wet ground to limiting dust spread or protecting a specific area.



Four mats, one system. GroundTuff mats spread loads evenly, reduce the risk of slips and accidents, and give a cost-effective, adaptable surface for a wide range of environments. They are widely used across the hire industry, on construction sites and at events – and Maltaward delivers them nationwide, 24/7.

GroundTuff

GP3248BL



- **Size:** 800 × 1200mm, 22mm thick (3' x 4')
- **Weight:** 22kg
- **Material:** 100% recycled PVC
- **Load capacity:** up to 20 tonnes*
- **Finish:** square top pattern on the top face
- **Application:** construction sites, events and car parking; good for wheeled use

Mats interlock to join; bevels available separately for a ramped edge.

GroundTuff Urban

GP4396BL-8



- **Size:** 1100 × 2400mm, 8mm thick
- **Weight:** 24kg
- **Material:** 100% recyclable HDPE
- **Load capacity:** up to 35 tonnes*
- **Finish:** 4-bar chequer plate and smooth face
- **Application:** pedestrian walkways, construction sites, events, car parking, access routes

Compatible with all connectors. 50 per stillage.

GroundTuff PRO

GP4896BL



- **Size:** 1200 × 2400mm, 12.7mm thick (8' x 4')
- **Weight:** 37.5kg
- **Material:** 100% recyclable HDPE
- **Load capacity:** up to 60 tonnes*
- **Finish:** 4-bar chequer and 1-bar chequer faces
- **Application:** construction and groundwork cover, events, temporary roadways, car parks

Compatible with all connectors. 35 per stillage.

GroundTuff Enviro

GP4896BL-15



- **Size:** 1230 × 2430mm, 15mm thick (8' x 4')
- **Weight:** 44kg
- **Material:** 95% recycled PVC
- **Load capacity:** up to 100 tonnes*
- **Finish:** 6-bar chequer plate on both sides
- **Application:** construction sites, events, car parking, access routes

Compatible with all connectors except the 2-way Low Profile. 30 per stillage.

MALTAWARD





GroundTuff Connectors

2-way Standard Connector
GPCB-2



4-way Standard Connector
GPCB-4




2-way Low Profile Connector
GPCL-2



2-way Galvanised Connector
GPCG-2



4-way Galvanised Connector
GPCG-4



Heavy Duty Cable Ties
GPCT



GroundTuff Storage

Stillage GPS4896BU · forklift-friendly storage and transport





The ground beneath the matting must be structurally sound and free from significant depressions, such as potholes, as these can cause the matting to crack or become damaged. *Load bearing capacity is dependent on ground conditions and load characteristics.

Talk to us about hiring the right mat for your site.

0800 043 2742
sales@maltaward.co.uk
www.maltaward.co.uk